

## Typical Applications

- Integrated Starter Alternator
- 42 Volts Automotive Electrical Systems


## Benefits

- Advanced Process Technology
- Ultra Low On-Resistance
- Dynamic dv/dt Rating
- 175°C Operating Temperature
- Fast Switching
- Repetitive Avalanche Allowed up to  $T_{jmax}$

## Description

Specifically designed for Automotive applications, this Stripe Planar design of HEXFET® Power MOSFETs utilizes the latest processing techniques to achieve extremely low on-resistance per silicon area. Additional features of this HEXFET power MOSFET are a 175°C junction operating temperature, fast switching speed and improved repetitive avalanche rating. These benefits combine to make this design an extremely efficient and reliable device for use in Automotive applications and a wide variety of other applications.


## HEXFET® Power MOSFET



$$V_{DS} = 75V$$

$$R_{DS(on)} = 0.0078\Omega$$

$$I_D = 130A^{\circ}$$



TO-220AB

## Absolute Maximum Ratings


|                            | Parameter                                  | Max.                     | Units |
|----------------------------|--------------------------------------------|--------------------------|-------|
| $I_D @ T_C = 25^{\circ}C$  | Continuous Drain Current, $V_{GS} @ 10V$   | 130 <sup>⑥</sup>         | A     |
| $I_D @ T_C = 100^{\circ}C$ | Continuous Drain Current, $V_{GS} @ 10V$   | 92 <sup>⑥</sup>          |       |
| $I_{DM}$                   | Pulsed Drain Current <sup>①</sup>          | 520                      |       |
| $P_D @ T_C = 25^{\circ}C$  | Power Dissipation                          | 330                      | W     |
|                            | Linear Derating Factor                     | 2.2                      | W/°C  |
| $V_{GS}$                   | Gate-to-Source Voltage                     | $\pm 20$                 | V     |
| $E_{AS}$                   | Single Pulse Avalanche Energy <sup>②</sup> | 390                      | mJ    |
| $I_{AR}$                   | Avalanche Current <sup>①</sup>             | See Fig.12a, 12b, 15, 16 | A     |
| $E_{AR}$                   | Repetitive Avalanche Energy <sup>②</sup>   |                          | mJ    |
| dv/dt                      | Peak Diode Recovery dv/dt <sup>③</sup>     | 4.6                      | V/ns  |
| $T_J$                      | Operating Junction and                     | -55 to + 175             | °C    |
| $T_{STG}$                  | Storage Temperature Range                  |                          |       |
|                            | Soldering Temperature, for 10 seconds      | 300 (1.6mm from case )   |       |
|                            | Mounting Torque, 6-32 or M3 screw          | 10 lbf•in (1.1N•m)       |       |

## Thermal Resistance

|                 | Parameter                           | Typ. | Max. | Units |
|-----------------|-------------------------------------|------|------|-------|
| $R_{\theta JC}$ | Junction-to-Case                    | —    | 0.45 | °C/W  |
| $R_{\theta CS}$ | Case-to-Sink, Flat, Greased Surface | 0.50 | —    |       |
| $R_{\theta JA}$ | Junction-to-Ambient                 | —    | 62   |       |

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

|                                 | Parameter                            | Min. | Typ. | Max.   | Units    | Conditions                                                                  |
|---------------------------------|--------------------------------------|------|------|--------|----------|-----------------------------------------------------------------------------|
| $V_{(BR)DSS}$                   | Drain-to-Source Breakdown Voltage    | 75   | —    | —      | V        | $V_{GS} = 0V, I_D = 250\mu A$                                               |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient  | —    | 0.09 | —      | V/°C     | Reference to $25^\circ\text{C}$ , $I_D = 1mA$                               |
| $R_{DS(on)}$                    | Static Drain-to-Source On-Resistance | —    | —    | 0.0078 | $\Omega$ | $V_{GS} = 10V, I_D = 78A$ ④                                                 |
| $V_{GS(th)}$                    | Gate Threshold Voltage               | 2.0  | —    | 4.0    | V        | $V_{DS} = 10V, I_D = 250\mu A$                                              |
| $g_{fs}$                        | Forward Transconductance             | 74   | —    | —      | S        | $V_{DS} = 25V, I_D = 78A$                                                   |
| $I_{DSS}$                       | Drain-to-Source Leakage Current      | —    | —    | 20     | $\mu A$  | $V_{DS} = 75V, V_{GS} = 0V$                                                 |
|                                 |                                      | —    | —    | 250    |          | $V_{DS} = 60V, V_{GS} = 0V, T_J = 150^\circ\text{C}$                        |
| $I_{GSS}$                       | Gate-to-Source Forward Leakage       | —    | —    | 200    | nA       | $V_{GS} = 20V$                                                              |
|                                 | Gate-to-Source Reverse Leakage       | —    | —    | -200   |          | $V_{GS} = -20V$                                                             |
| $Q_g$                           | Total Gate Charge                    | —    | 160  | 250    | nC       | $I_D = 78A$                                                                 |
| $Q_{gs}$                        | Gate-to-Source Charge                | —    | 35   | 52     |          | $V_{DS} = 60V$                                                              |
| $Q_{gd}$                        | Gate-to-Drain ("Miller") Charge      | —    | 54   | 81     |          | $V_{GS} = 10V$ ④                                                            |
| $t_{d(on)}$                     | Turn-On Delay Time                   | —    | 11   | —      | ns       | $V_{DD} = 38V$                                                              |
| $t_r$                           | Rise Time                            | —    | 150  | —      |          | $I_D = 78A$                                                                 |
| $t_{d(off)}$                    | Turn-Off Delay Time                  | —    | 150  | —      |          | $R_G = 2.5\Omega$                                                           |
| $t_f$                           | Fall Time                            | —    | 140  | —      |          | $V_{GS} = 10V$ ④                                                            |
| $L_D$                           | Internal Drain Inductance            | —    | 4.5  | —      | nH       | Between lead,<br>6mm (0.25in.)<br>from package<br>and center of die contact |
| $L_S$                           | Internal Source Inductance           | —    | 7.5  | —      |          |                                                                             |
| $C_{iss}$                       | Input Capacitance                    | —    | 5600 | —      | pF       | $V_{GS} = 0V$                                                               |
| $C_{oss}$                       | Output Capacitance                   | —    | 890  | —      |          | $V_{DS} = 25V$                                                              |
| $C_{rss}$                       | Reverse Transfer Capacitance         | —    | 190  | —      |          | $f = 1.0KHz$ , See Fig. 5                                                   |
| $C_{oss}$                       | Output Capacitance                   | —    | 5800 | —      |          | $V_{GS} = 0V, V_{DS} = 1.0V, f = 1.0KHz$                                    |
| $C_{oss}$                       | Output Capacitance                   | —    | 560  | —      |          | $V_{GS} = 0V, V_{DS} = 60V, f = 1.0KHz$                                     |
| $C_{oss \text{ eff.}}$          | Effective Output Capacitance ⑤       | —    | 1100 | —      |          | $V_{GS} = 0V, V_{DS} = 0V \text{ to } 60V$                                  |




## Source-Drain Ratings and Characteristics

|          | Parameter                                 | Min.                                                                        | Typ. | Max. | Units | Conditions                                                              |
|----------|-------------------------------------------|-----------------------------------------------------------------------------|------|------|-------|-------------------------------------------------------------------------|
| $I_S$    | Continuous Source Current<br>(Body Diode) | —                                                                           | —    | 130  | A     | MOSFET symbol<br>showing the<br>integral reverse<br>p-n junction diode. |
| $I_{SM}$ | Pulsed Source Current<br>(Body Diode) ①   | —                                                                           | —    | 520  |       |                                                                         |
| $V_{SD}$ | Diode Forward Voltage                     | —                                                                           | —    | 1.3  | V     | $T_J = 25^\circ\text{C}, I_S = 78A, V_{GS} = 0V$ ④                      |
| $t_{rr}$ | Reverse Recovery Time                     | —                                                                           | 110  | 170  | ns    | $T_J = 25^\circ\text{C}, I_F = 78A$                                     |
| $Q_{rr}$ | Reverse Recovery Charge                   | —                                                                           | 390  | 590  | nC    | $di/dt = 100A/\mu s$ ④                                                  |
| $t_{on}$ | Forward Turn-On Time                      | Intrinsic turn-on time is negligible (turn-on is dominated by $L_S + L_D$ ) |      |      |       |                                                                         |


### Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 11).
- ② Starting  $T_J = 25^\circ\text{C}$ ,  $L = 0.13mH$   
 $R_G = 25\Omega$ ,  $I_{AS} = 78A$ . (See Figure 12).
- ③  $I_{SD} \leq 78A$ ,  $di/dt \leq 320A/\mu s$ ,  $V_{DD} \leq V_{(BR)DSS}$ ,  
 $T_J \leq 175^\circ\text{C}$
- ④ Pulse width  $\leq 400\mu s$ ; duty cycle  $\leq 2\%$ .


- ⑤  $C_{oss \text{ eff.}}$  is a fixed capacitance that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 80%  $V_{DSS}$ .
- ⑥ Calculated continuous current based on maximum allowable junction temperature. Package limitation current is 75A.
- ⑦ Limited by  $T_{Jmax}$ , see Fig.12a, 12b, 15, 16 for typical repetitive avalanche performance.




**Fig 1.** Typical Output Characteristics



**Fig 2.** Typical Output Characteristics







**Fig 3.** Typical Transfer Characteristics




**Fig 4.** Normalized On-Resistance vs. Temperature


# IRF1407

International  
**IR** Rectifier







**Fig 9.** Maximum Drain Current vs. Case Temperature



**Fig 10a.** Switching Time Test Circuit




**Fig 10b.** Switching Time Waveforms




**Fig 11.** Maximum Effective Transient Thermal Impedance, Junction-to-Case

# IRF1407


International  
**IR** Rectifier




**Fig 12a.** Unclamped Inductive Test Circuit




**Fig 12b.** Unclamped Inductive Waveforms




**Fig 13a.** Basic Gate Charge Waveform



**Fig 13b.** Gate Charge Test Circuit



**Fig 12c.** Maximum Avalanche Energy vs. Drain Current



**Fig 14.** Threshold Voltage vs. Temperature

www.irf.com




Fig 15. Typical Avalanche Current vs. Pulsewidth




Fig 16. Maximum Avalanche Energy vs. Temperature

**Notes on Repetitive Avalanche Curves , Figures 15, 16:  
(For further info, see AN-1005 at [www.irf.com](http://www.irf.com))**


1. Avalanche failures assumption:  
Purely a thermal phenomenon and failure occurs at a temperature far in excess of  $T_{jmax}$ . This is validated for every part type.
2. Safe operation in Avalanche is allowed as long as  $T_{jmax}$  is not exceeded.
3. Equation below based on circuit and waveforms shown in Figures 12a, 12b.
4.  $P_{D(ave)}$  = Average power dissipation per single avalanche pulse.
5. BV = Rated breakdown voltage (1.3 factor accounts for voltage increase during avalanche).
6.  $I_{av}$  = Allowable avalanche current.
7.  $\Delta T$  = Allowable rise in junction temperature, not to exceed  $T_{jmax}$  (assumed as 25°C in Figure 15, 16).  
 $t_{av}$  = Average time in avalanche.  
 $D$  = Duty cycle in avalanche =  $t_{av} \cdot f$   
 $Z_{thJC}(D, t_{av})$  = Transient thermal resistance, see figure 11)

$$P_{D(ave)} = \frac{1}{2} (1.3 \cdot BV \cdot I_{av}) = \frac{\Delta T}{Z_{thJC}}$$


$$I_{av} = \frac{2\Delta T}{1.3 \cdot BV \cdot Z_{thJC}}$$

$$E_{AS(AR)} = P_{D(ave)} \cdot t_{av}$$

## Peak Diode Recovery dv/dt Test Circuit



\* Reverse Polarity of D.U.T for P-Channel




\*\*\*  $V_{GS} = 5.0V$  for Logic Level and 3V Drive Devices

**Fig 17.** For N-channel HEXFET® power MOSFETs

## TO-220AB Package Outline


Dimensions are shown in millimeters (inches)



- NOTES:
- |                                                     |                                                      |
|-----------------------------------------------------|------------------------------------------------------|
| 1 DIMENSIONING & TOLERANCING PER ANSI Y14.5M, 1982. | 3 OUTLINE CONFORMS TO JEDEC OUTLINE TO-220AB.        |
| 2 CONTROLLING DIMENSION : INCH                      | 4 HEATSINK & LEAD MEASUREMENTS DO NOT INCLUDE BURRS. |

## TO-220AB Part Marking Information

EXAMPLE: THIS IS AN IRF1010  
LOT CODE 1789  
ASSEMBLED ON WW19, 1997  
IN THE ASSEMBLY LINE "C"



Data and specifications subject to change without notice.  
This product has been designed and qualified for the Automotive [Q101] market.  
Qualification Standards can be found on IR's Web site.

International  
**IOR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7903

Visit us at [www.irf.com](http://www.irf.com) for sales contact information.10/01